

**Product Description:**

Complete offering of 30A Switch-Rated IEC 60309 Pin & Sleeve receptacles, connectors and plugs. Available amperages will mirror Hubbell's standard industrial pin & sleeve offering. Devices are certified to UL2682 as an approved motor disconnect and general purpose branch disconnect. UL witnessed testing to maintain a UL Type 4X, 12 and IP69k environmental rating.

**Key Feature****IEC 60309 Rated Product****UL 2682 Rated Device****Continuous Ground Engagement****UL Witnessed IP69k & Type 4X, 12****Power Indicating LED Lights****Permanent Labelless Markings****Key Benefits**

Mates with existing installed base of IEC 60309.

Higher HP Rating &amp; SCCR allow device to be used as Motor/Branch Disconnect.

Unswitched feed-thru ground is first to mate and last to break.

Superior Water Ingress Protection

LEDs on both side of the device provide visual verification of power.

Ratings laser marked onto the device and will not wash off.

**Market Strategy:**

Revisit all IEC 60309 customers that have bought an IEC 60309 connector or receptacle (that are not using a mechanical interlock). Educate customers on UL2682 and our increased horsepower ratings (up to 30HP) and a SCCR of 100kA when in use with class J fuse. Heavy focus on the fact that our devices mate with existing installed base of IEC 60309 devices.

**Targets:**

Industrial / Manufacturing

Food Processing

Motor Connections

Water Processing

**Replacement Items:**

Weatherproof Covers

Cord Clamp

**Competition:**

None in IEC 60309 Market.

**Complimentary Products:**

Standard IEC Pin &amp; Sleeve Back Boxes

Liquidtight Conduit Adapters

Meltric is the only other manufacturer with UL2682 Switch-Rated Connections

**Applications:**

Motor Disconnect and General Purpose Branch Disconnect.

Everywhere you sell standard pin &amp; sleeve

Cord Drop

Wet/Wash Down Environments

**Agency Listings:**

cULus LISTED

UL CLASSIFIED

**Specifications:****Electrical:** 30A 125V up to 600V**Material:** Valox (Housing), Brass (Pins & Sleeves), SS (Hardware)**Environmental:** UL Type 4X, 12 and IP69k**Vocabulary/Industry Terms/FAQ's:****Q:** Does this mean that your standard pin & sleeve is not rated as a motor disconnect?**A:** No. Our standard pin & sleeve is HP rated. We have simply increased the HP rating from 7.5 on our standard industrial pin & sleeve to a possible 30HP with the Advantage™ series depending on the configuration.**Q:** Will you mate with Meltric?**A:** No, Meltric is a proprietary configuration. We are an IEC 60309 pin and sleeve and will mate with all manufacturers in the IEC 60309 category.**Q:** Is your product arc flash rated?**A:** There is no such rating for electrical plugs and connectors. Hubbell standard industrial pin & sleeve, Meltric and the Advantage™ Series are all considered dead face devices.**Q:** Do you have equal switching capabilities as Meltric?**A:** No, Hubbell's HP rating far exceed competition's.